

[54] **ELECTROMAGNETIC SHIELD FOR ELECTRONIC EQUIPMENT**

[75] Inventors: Warren D. Coats, Newberg, Oreg.;  
Marc A. Kamerling, Santa Rosa,  
Calif.

[73] Assignee: Tektronix, Inc., Beaverton, Oreg.

[21] Appl. No.: 164,874

[22] Filed: Jul. 1, 1980

[51] Int. Cl.<sup>3</sup> ..... H05K 9/00

[52] U.S. Cl. .... 174/35 R; 358/245

[58] Field of Search ..... 174/35 MS, 35 R;  
358/245, 247; 219/10.55 D; 313/313, 402, 408

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

2,673,342 3/1954 Sims, Jr. et al. .... 358/245  
3,952,152 4/1976 Lill et al. .... 358/245  
4,008,383 2/1977 Tanaka et al. .... 219/10.55 D  
4,051,341 9/1977 Tanaka et al. .... 174/35 MS X

4,246,613 1/1981 Choder et al. .... 358/245  
4,247,737 1/1981 Johnson et al. .... 174/35 MS

*Primary Examiner*—A. T. Grimley

*Assistant Examiner*—D. A. Tone

*Attorney, Agent, or Firm*—Thomas J. Spence; John H. Bouchard

[57] **ABSTRACT**

A substantially transparent interference shield wherein a flexible material employed to form an interlayer laminating a thin metal screen between two panels of glass is extended beyond the periphery of the panels a distance less than the screen so as to provide the necessary support permitting the shield to be mounted in a surrounding frame solely by clamping engagement of the extended screen. Provision is also made for the additional encapsulation within the flexible material of a resilient gasket employed to enhance electrical contact between the screen and the frame.

15 Claims, 7 Drawing Figures

